

## Efficiency of a Carnot Engine at Maximum Power Output

F. L. CURZON

B. AHLBORN

*Department of Physics**University of British Columbia**Vancouver, B.C., Canada*

(Received 9 November 1973; revised 14 May 1974)

*The efficiency of a Carnot engine is treated for the case where the power output is limited by the rates of heat transfer to and from the working substance. It is shown that the efficiency,  $\eta$ , at maximum power output is given by the expression  $\eta = 1 - (T_2/T_1)^{1/2}$  where  $T_1$  and  $T_2$  are the respective temperatures of the heat source and heat sink. It is also shown that the efficiency of existing engines is well described by the above result.*

### INTRODUCTION

It is well known that practical heat engines are not as efficient as the classical Carnot cycle. Standard texts point out that inefficiencies occur because of heat leaks, or degradation of kinetic energy into heat by means of friction, etc.<sup>1-3</sup>

We have found it instructive in our classes on thermodynamics to consider another fundamental limitation on efficiency which is caused by the rate at which heat can be exchanged between the working material and the heat reservoirs.

To achieve the theoretical efficiency, the isothermal parts of the cycle have to be carried out infinitely slowly so that the working substance can come into thermal equilibrium with the heat reservoirs (i.e., no temperature gradients occur across the walls of the container which encloses the working material). Under these conditions the power output is clearly zero since it takes an infinite time to do a finite amount of work.

To obtain a finite power output the cycle is speeded up. However, to drive the heat flux during the isothermal expansion of the working substance, the substance must be colder than the heat source. Conversely, during the isothermal compression the working substance cannot reject heat to the sink unless it is hotter than the sink. Ultimately, the two isothermal stages take place with no change in temperature of the working substance, so that heat flows straight from the source to the sink, and no mechanical work is performed by the engine. Hence the power output is zero and the engine has zero efficiency. Somewhere between these two extremes of zero power (i.e., optimum or zero efficiency) the engine clearly has a maximum power output. The efficiency under conditions of maximum power output is evaluated below.

### THEORETICAL MODEL

We assume that heat fluxes through the vessel containing the working substance are proportional to the temperature difference across the walls of the vessel. In the isothermal expansion stage we therefore have

$$F_1 = \alpha(T_1 - T_{1w}) \quad (1)$$

where  $F_1$  is the heat flux,  $\alpha$  is a constant depending on the thickness and thermal conductivity of the wall;  $T_1$  is the temperature of the heat source and  $T_{1w}$ , the temperature of the working substance. If the isothermal expansion lasts  $t_1$  seconds, the input energy  $W_1$  is

$$W_1 = F_1 t_1 = \alpha t_1 (T_1 - T_{1w}). \quad (2)$$

We assume the adiabatic expansion is completely reversible (no heat exchanges with the surroundings). On the isothermal compression, heat  $W_2$  is rejected to the heat sink where

$$W_2 = \beta t_2 (T_{2w} - T_2). \quad (3)$$

In the above equation  $t_2$  is the duration of the compression,  $T_2$  is the temperature of the heat sink,  $\beta$ , its heat transfer coefficient, and  $T_{2w}$  the temperature of working material. The final adiabatic compression brings the working substance back to its original volume and temperature.

Since the adiabatic stages are reversible, we must have that

$$(W_1/T_{1w}) = (W_2/T_{2w})$$

i.e.,

$$(t_1/t_2) = \beta T_{1w}(T_{2w} - T_2)/T_{2w}\alpha(T_1 - T_{1w}) \quad (4)$$

(see Eqs. 2 and 3 above).

The power ( $P$ ) of the engine is then given by the expression

$$P = (W_1 - W_2)/(t_1 + t_2)\gamma, \quad (5)$$

where  $(\gamma - 1)(t_1 + t_2)$  is the time taken to complete the adiabatic cycles. Hence we assume that as the heat engine is speeded up, the time to complete the adiabatic processes remains proportional to the time required for the isothermal processes.

Using Eq. (4) to eliminate  $t_1/t_2$  leads to the results

$$P = \frac{\alpha\beta xy(T_1 - T_2 - x - y)}{\gamma[\beta T_1 y + \alpha T_2 x + xy(\alpha - \beta)]}, \quad (6)$$

$$x = T_1 - T_{1w}, \quad y = T_{2w} - T_2. \quad (7)$$

$P$  is maximized by values of  $x$  and  $y$  satisfying the following equations:

$$(\partial P/\partial x) = 0,$$

i.e.,

$$\begin{aligned} \beta T_1 y(T_1 - T_2 - x - y) \\ = x[\beta T_1 y + \alpha T_2 x + xy(\alpha - \beta)] \end{aligned} \quad (8a)$$

$$(\partial P/\partial y) = 0,$$

i.e.,

$$\begin{aligned} \alpha T_2 x(T_1 - T_2 - x - y) \\ = y[\beta T_1 y + \alpha T_2 x + xy(\alpha - \beta)]. \end{aligned} \quad (8b)$$

From this it follows that

$$y = (\alpha T_2/\beta T_1)^{1/2} x \quad (9)$$

which is then used to eliminate  $y$  from Eq. (8a) to give the following quadratic equation for  $x/T_1 = \mu$ :

$$\begin{aligned} [1 - (\alpha/\beta)]\mu^2 - 2[(\alpha T_2/\beta T_1)^{1/2} + 1]\mu \\ + [1 - (T_2/T_1)] = 0. \end{aligned} \quad (10)$$

Since  $\mu < 1$ , the physically relevant solution of this equation is readily shown to be:

$$\mu = \frac{x}{T_1} = \frac{1 - (T_2/T_1)^{1/2}}{1 + (\alpha/\beta)^{1/2}}. \quad (11)$$

From Eq. (9) it follows that

$$\frac{y}{T_2} = \frac{(T_1/T_2)^{1/2} - 1}{1 + (\beta/\alpha)^{1/2}}. \quad (12)$$

The efficiency of the engine ( $\eta'$ ) at maximum power is given by

$$\begin{aligned} \eta' &= (W_1 - W_2)/W_1 \\ &= 1 - (T_{2w}/T_{1w}) \\ &= 1 - [(T_2 + y)/(T_1 - x)]. \end{aligned} \quad (13)$$

Using Eqs. (11) and (12) to eliminate  $x$  and  $y$  from the expressions for  $\eta'$  leads to the result

$$\eta' = 1 - (T_2/T_1)^{1/2}. \quad (14)$$

At maximum power, it follows from Eqs. (4) and (7) that

$$(t_1/t_2) = \beta T_{1w} y / \alpha T_{2w} x. \quad (15)$$

Eliminating  $(y/x)$  by using Eq. (9) and noting that  $T_{2w}/T_{1w} = (T_2/T_1)^{1/2}$  [see Eq. (14)] leads to the conclusion that

$$t_1/t_2 = (\beta/\alpha)^{1/2}. \quad (16)$$

From Eqs. (11) and (12), the working temperatures in the isothermal parts of the Carnot cycle

TABLE I. Observed performance of real heat engines.

Power source	$T_2$ (°C)	$T_1$ (°C)	$\eta$ (Carnot)	$\eta'$ (Eq. 14)	$\eta$ (observed)
West Thurrock (U.K.) <sup>2</sup> Coal Fired Steam Plant	~25	565	64.1%	40%	36%
CANDU (Canada) <sup>4</sup> PHW Nuclear Reactor	~25	300	48.0	28%	30%
Larderello (Italy) <sup>5</sup> Geothermal Steam Plant	80	250	32.3%	17.5%	16%

are:

$$T_{1w} = CT_1^{1/2}, \quad T_{2w} = CT_2^{1/2}, \quad (17)$$

where

$$C = [(\alpha T_1)^{1/2} + (\beta T_2)^{1/2}] / [(\alpha)^{1/2} + (\beta)^{1/2}]. \quad (18)$$

Finally, using the above equations, it is readily shown that the maximum power ( $P_{\max}$ ) is

$$P_{\max} = (\alpha\beta/\gamma) [(T_1^{1/2} - T_2^{1/2}) / (\alpha^{1/2} + \beta^{1/2})]^2. \quad (19)$$

The most interesting feature of the above results is Eq. (14) which shows that the efficiency does not depend on the heat transfer coefficients ( $\alpha$  and  $\beta$ ), and has the attractive feature, that, as with the efficiency for an ideal Carnot engine [ $\eta = 1 - (T_2/T_1)$ ] it depends only on the temper-

ature of the heat reservoirs. However the result also has the interesting property that it serves as quite an accurate guide to the best observed performance of real heat engines, as is shown by Table I.

<sup>1</sup> G. J. Van Wylen and R. E. Sonntag, *Fundamentals of Classical Thermodynamics* (Wiley, New York, 1973), 2nd ed., pp. 170-195.

<sup>2</sup> D. B. Spalding and E. H. Cole, *Engineering Thermodynamics* (Edward Arnold, London, 1966), 2nd ed., pp. 200-286, table on p. 209.

<sup>3</sup> B. D. Wood, *Applications of Thermodynamics* (Addison Wesley, London, Ontario, 1969), pp. 1-86. See also the list of standard texts given on p. xv of this book.

<sup>4</sup> G. M. Griffiths, *Phys. Can.* **30**, 2 (1974); reference to efficiency is on p. 5.

<sup>5</sup> A. Chierici, *Planning of a Geothermal Power Plant: Technical and Economic Principles* (U. N. Conference on New Sources of Energy, New York, 1964), Vol. 3, pp. 299-311.